


Specifications of aluminum busbars for distribution boxes



Overview

Aluminum Busbar Grades and Specifications Welcome to AP Precision Metals' comprehensive guide on aluminum busbar grades and specifications. Aluminum busbar.

Key Takeaways

Aluminum busbars in distribution boxes are designed for high conductivity, lightweight handling, and compliance with IEC 61439 standards, with specifications including alloy type, current rating, temperature limits, and mechanical dimensions. Material and Alloy Types

Aluminum busbars are typically made from electrical-grade aluminum alloys such as 1050, 1060, 6101, and 6061, chosen for their high electrical conductivity, corrosion resistance, and mechanical strength. Some systems also use copper-clad aluminum (CCA) for enhanced conductivity while maintaining a lightweight profile. The choice of alloy affects the busbar's ampacity, thermal performance, and flexibility for bending or punching during installation .

Electrical Ratings

- Voltage Rating: Aluminum busbars in low-voltage distribution boxes are rated up to 1000 V AC and 1500 V DC according to IEC 61439 standards .



- **Current Rating (Ampacity):** The busbar must carry the continuous load without exceeding permissible temperature rise. Ratings vary depending on cross-sectional area, alloy, and installation conditions. For example, busbars in industrial applications can range from 160 A to 5000 A for aluminum conductors .

- **Short-Circuit Withstand:** Busbars are designed to handle fault currents safely, with sizing calculations based on IEC 61439 and IEC 60287 standards .

Thermal and Environmental Specifications

- **Temperature Rise:** The maximum working temperature is typically 140°C, which is 105 K above an ambient of 35°C, ensuring safe operation under continuous load .

- **Ambient Conditions:** Busbars are tested for corrosion resistance, electromagnetic compatibility, and degree of protection (IP rating). Common protection levels include IP20 for small distribution boxes and IP55 or higher for industrial busbar trunking systems .

Mechanical Dimensions and Construction

- **Cross-Section:** Determined by current-carrying requirements and space constraints. Aluminum busbars are available in solid, laminated, flexible, or roll forms .

- **Customization:** Busbars can be bent, punched, cut, or terminal-processed to fit specific distribution box layouts, reducing secondary processing costs .

- **Conductors:** Systems may include 3, 4, or 5 conductors, depending on the application and phase requirements .

Compliance and Testing

Aluminum busbars must comply with IEC 61439-1 and 61439-6 standards, which cover low-voltage switchgear and busbar trunking systems. Compliance ensures proper thermal limits, mechanical strength, and electrical performance. Verification can be done by type testing, calculation, or comparison with reference projects, and manufacturers provide assembly instructions to guarantee conformity .

Summary

When selecting aluminum busbars for distribution boxes, key specifications include:

- Alloy type: 1050, 1060, 6101, 6061, or CCA
- Voltage rating: Up to 1000 V AC / 1500 V DC
- Current rating: Based on ampacity and system load (160–5000 A)
- Temperature rise: Max 140°C under continuous load
- Mechanical form: Solid, laminated, flexible, or roll
- Protection rating: IP20–IP55 or higher

- Compliance: IEC 61439 standards for low-voltage assemblies These specifications ensure safe, efficient, and reliable power distribution while allowing flexibility for installation and system design.

Article Content

TECHNICAL SPECIFICATION

5.11 HT cable termination box shall be provided with a silica gel breather.
Distribution Transformer shall comply with the latest IS

Contact Us

Continue your research online:

Website: <https://coetzerinvestments.co.za>

Technical inquiry: <https://coetzerinvestments.co.za/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

